

26" / 32" / 42" Display Digital Signage

- All-in-one Design
- Easy Field Service (Swappable tray design and isolated)
- Shallow Compact Form Factor
- Reliable & Stable
- Well cabling management
- Build in CF reader media player and software
- Build in speakers



Signage PC Display with Media Player

Display Resolution	26"	32"	42"
Display Resolution	1366 x 768 WXGA	1366 x 768 WXGA	1920 x 1080 Full HD
Aspect Ratio (W:H)	16:9		
Recommended Resolution	1366 x 768 @ 60Hz	1366 x 768 @ 60Hz	1920 x 1080 @ 60Hz
Protection	Tempered glass (option)		4mm Tempered glass
Cabinet Dimensions* (WxHxD)	676 x 420 x 90 mm	796 x 491 x 136 mm	1045 x 638 x 126.1 mm
Screen Brightness	500 nits		
Response Time	8ms GTG	6.5ms GTG	
Contrast Ratio	1500:1		
Full Viewing Angle	176°(H) / 176°(V)	178°(H) / 178°(V)	
Colors	16.7 million		
Line Voltage	100-240VAC 50/60Hz (auto)		
Power Consumption	115watts	150watts	240watts
DDC	DDC 2B		
Operating Temperature	0~50°C		
Operating Humidity	10~85% RH non-condensing		
Video Input	VGA x 1, DVI x 1, Composite x 1		
Speakers	10+10W Speakers, built-in amplifier		
Media Reader	Compact Flash Reader x 1		
Content			
Video Format Support	MPEG1, MPEG2, MPEG4**		
Graphics Format Support	JPEG		

* Weight and dimensions are approximate.

** CF card is recommended when playing MPEG2 Video

