



Model	VIPER32OUT	VIPER42OUT	VIPER55OUT
	32"(697 392mm)	42"(930 *523mm)	55"(1209 *680mm)
Display Ratio	16:9	16:9	16:9
Resolution	1920*1080 Full HD	1920*1080 Full HD	1920*1080 Full HD
Brightness	1500 cd/m ²	1500 cd/m ²	2000 cd/m ²
Contrast Ratio	3000:1	3000:1	3000:1
Viewing Angle	178 ° / 178 °	178 ° / 178 °	178 ° / 178 °
Operation Parameters			
Video Interface	VGA HDMI CVBS S-Video	VGA HDMI CVBS S-Video	VGA HDMI CVBS S-Video
Audio Interface	Input and output	Input and output	Input and output
Brightness Control	Automatic light sensor system	Automatic light sensor system	Automatic light sensor system
Temperature Control System	Precise air conditioner	Precise air conditioner	Precise air conditioner
Operating Temperature	-20°C to +45°C	-20°C to +45°C	-20°C to +45°C
Operating Humidity	5% to 100%	5% to 100%	5% to 100%
Power Supply	AC 108-115V	AC 108-115V	AC 108-115V
	AC 208-240V	AC 208-240V	AC 208-240V
Max Consumption	400w	500w	600w
Waterproof Enclosure			
Protection Grade	IP55	IP55	IP55
Package Size (W*H*D)	950*840*350mm	1180*1000*350 mm	1460*1130*350 mm
Gross weight	138kg	166kg	198kg
Installation	Back hanging or customized	Back hanging or customized	Back hanging or customized
Protection Glass	6mm AR safe glass	6mm AR safe glass	6mm AR safe glass
Optional Configurations			
Advertising Industry	Network version of embedded decoding play system		
Professional Display Industry	Embedded PC and information distribution system		
Touch Screen	IR waterproof anti-glare touch screen		