Code 3069



21,5" 10 point touch monitor with edge-to-edge glass and AMVA panel

With its Full HD (1920x1080) resolution and accurate Projective Capacitive 10 point touch technology, the 3069 Monitor delivers seamless and accurate touch response. The AMVA panel technology guaranteeshighperformancewithexcellentcolourreproductionandhigh contrast, making it an excellent choice for a vast array of demanding interactive applications. The flexible stand can be positioned at several angles, or laid flat on a surface, creating a comfortable and ergonomic userexperience. The 3069 Monitoristheidealscreenforagreat Windows8 touch-experience.

DISPLAY CHARACTERISTICS

Diagonal	21.5"; 55cm
Touchtechnology	projective capacitive, multitouch (10 compatible touch points - HID, only with supported OS), activated by finger
Panel	AMVA LED
Glass thickness	2.4 mm
Glass hardness	7H minimum
Display area h x w	476.6 x 268.1 mm; 18.8" x 10.6 "
Response time	12 ms
Advanced contrast	5 000 000 : 1 ACR
Static contrast	3 000 : 1 with touch panel
Brightness	225 cd/m² with touch panel
Viewing zone	horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 80 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Light transmittance	90%

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	23 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS

EU ENERGY EFFICIENCY LABEL

Energy efficiency class	В
On Mode Power Consumption	23.3W
Annual Energy Consumption	34 kW/annum*
Visible Screen Diagonal	55 cm: 22"

This is information under Regulation (EU) No 1062/2010.

*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.

DIMENSIONS / WEIGHT

Dimensions w x h x d	522.5 x 128 (385) x 238.5 mm
Weight	6.6 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, HDMI
Inputs	USB (for touch connectivity), USB 3.0
USB hub	UP 1 x USB 3.0 / DOWN 4 x USB 3.0

SPECIAL FEATURES

PECIAL FEAT	JRES	
	Plug & Play	VESA DDC2B™
	Controls	On-Screen-Display in 9 languages (EN, FR, DE, ES, IT, PT, RU, JP, Chinese simplified) and 5 front controls (Scroll up / Audio Adjust, Scroll down / ECO, Auto, Menu, Power)
	User controls	luminance (contrast, brightness, ECO, i-Style colour, ACR), image setup (clock, phase, H.position, V.position, aspect), colour temp., OSD setup (H.position, V. position, timeout, language), extra (reset, signal select, HDMI audio, OD, information), volume, auto adjust
	Speakers	2 x 2 W (Stereo)
	Anti-theft-device	Kensington-lock™ prepared
	Safety	CE, TÜV-Bauart, CU
	Height adjustable stand	Yes
	Height adjustment	257 mm
	Tilt angle	90° up; 5° down
	VESA mounting	100 x 100 mm
	Colour	Black

ACCESORIES

Driv	ver multi-touch: Windows7/8 (HID complian	nt)
Included accessorie	s power cable, VGA (D-Sub) signal cable DVI-D signal cable, audio cable, USB cal quick start guide, safety guide	

